## cossiga



## Drainage System Options


- Plastic bottle -manual empty
- Pump to waste
- Electronic evaporator pan


- Stainless steel construction
- Four adjustable shelves
- Ticket strips on shelves
- Shelf mounted air curtains
- Under shelf and canopy LED lights
- Pull down night blind
- Forced air circulation
- Integral condenser
- Removable front grille panel
- Roll in on castors
- Climate class M1
- Hinged front door optional





Shown with optional frameless hinged acrylic front door

sold as accessory kit









## **CABINET DIMENSIONS & SPECIFICATIONS**

Prior to installation see installation guidelines ventilation requirements and drainage ontions documents

	Thorto instattation see, instatta														ion galactines, ventitation requirements and drainage options accuments						
MODEL	CABINET				SHELVING	OPERATING TEMP	SHELF	BASE TRAY	DISPLAY	REFRIGERANT	FREQUENCY	OPERATING CURRENT	ENERGY CONSUMPTION	CONNEC ELECTRICAL POWE		VOLTAGE	F	PACKED FOR SHIPPING			
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											NZ/AUS 10 AMP							
DTGOR6	600	775	1860	170	4 + BASE	-1 +5	486 X 386	520 x 453	0.98	R290	50/60 HZ	1.0 / 5.5 (PTC)	14.86	3 PIN PLUG	3 PIN PLUG	220-240V	700	830	2030	180	

Maximum shelf load weight 15kg spread evenly

25



